



BOSTIK ROLL

REINFORCED DOUBLE-SIDED ADHESIVE TAPE

Fact Sheet No.: TDS01945

Date: 22 September 2021

YOUR SMART ADVANTAGES

- Solvent-free adhesive tape
- Instant grab
- Clean & easy installation

USES

Bostik Roll is a high strength adhesive tape that is suitable for the fast installation of soft textile and resilient floor coverings, all types of skirting, capping strips, coving and other floor or lightweight wall mounted accessories. It can be used as a direct alternative to traditional solvent and water-based adhesives.

The double-sided tape is quick, easy and clean to use, offering an instantaneous grab with a pressure sensitive bond. Bostik Roll is solvent-free and does not leave behind vapour often associated with traditional contact adhesives. It will not discolour bonded materials and offers excellent plasticiser migration resistance, making it particularly suited for use with PVC products.

The product is used to bond a wide range of materials such as textile and resilient flooring and lightweight wall accessories to sound and strong substrates.

Bostik Roll is available in 3 sizes, enabling complex applications to be carried out.

As it's solvent-free, Bostik Roll is an environmentally friendly option that has less impact on the building occupants. It achieves A+ and ECI Plus ratings with LEED and EN 13999:2007 for BREEAM, thanks to its very low VOC emissions.

PRODUCT CHARACTERISTICS

Form	Self-adhesive tape
Composition	Pre-coating based on synthetic resins and reinforced weft

Product Codes	30607844 25mm x 50m 30607845 50mm x 50m 30607846 85mm x 50m 30607857 240mm x 25m
Storage/Shelf Life	Store for up to 18 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +10°C to +30°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (approx.)

Application Temperature	+10°C to +30°C
Open Times	Unlimited
Drying Times	Ready for immediate use
Foot traffic	Ready for immediate use
Curing time	Ready for immediate use

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Roll, refer to the relevant Health and Safety Data Sheet, available at www.bostik.com/uk.

All phases of installation should comply with the latest editions of:

- BS 8102 Code of Practice for protection of building against water from the ground.
- BS 5325 Code of Practice for the installation of textile floor coverings.
- BS 8203 Code of Practice for the installation of resilient floor coverings.

PREPARATION

1. Ensure the substrate is clean, sound, dry and free from contaminants that may hinder adhesion.
2. Any contaminants on either the wall or floor that may hinder adhesion, such as grease, dust, wallpaper, silicone sealants, some curing compounds and old adhesive residues should be completely removed.
3. Metal, plastic, previously applied adhesives or painted walls will need mechanically abrading to provide a key. If in doubt always carry out a trial to ensure compatibility.
4. Ensure any damaged walls or floors are made good and that there is a smooth, flat surface to apply Bostik Roll to.

PRIMING

5. Prime textured or porous surfaces as required with Bostik Universal Primer. Dense, compact surfaces should be lightly abraded and made dust free.
6. Do not use a solvented, aerosol primer as this can impair adhesion.

APPLICATION

7. Ensure that the surface is free from dust. Dust needs to be removed from the surface as it could hinder adhesion properties.
8. Allow the skirting and tape to acclimatise to room temperature prior to installation. Heating of skirting is not required.
9. Cold temperatures and damp sites can result in a condensate of water on the substrates and materials being applied, which will prevent adhesion. Ideal performance will be achieved in the temperature range +10°C and +30°C.
10. Bostik Roll must always be applied to the substrate, i.e. the floor or wall, and not on the floor covering or accessory.
11. Once applied to the substrate, the tape should be firmly compressed using a suitable hand roller.
12. Prior to removing the release paper, ensure all materials (capping, skirting, vinyl etc.) are cut to the appropriate size.
13. Remove the release paper and using controlled, consistent hand pressure, place the materials onto the Bostik Roll avoiding air entrapment. Once firmly in place, roller the materials to enhance the bond.
14. Bostik Roll offers an instant pressure sensitive bond enabling further processes to be carried out immediately.
15. In areas such as shower enclosures and wet rooms, it is essential that the design ensures water is kept away from the adhesive bond line and where necessary use a bead of suitable sealant.

PRECAUTIONS IN USE

For any application not covered, please contact Technical Services on +44 (0) 1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Roll, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com