

# ULTRATOP EASYCOLOR

Colouring solution for cementitious-based Ultratop Loft systems



## DESCRIPTION

**Ultratop Easycolor** are highly selected pre-dispersed pigments, which guarantee a high colouring capacity, according to a formulation developed in the MAPEI R&D laboratories.

When added to **Ultratop Loft F** and **Ultratop Loft W** cementitious mortars during their preparation, it is possible to create countless colour variations in order to satisfy the most varied requests of the end users.

## WHERE TO USE

In all civil, residential, commercial and retail building settings, whenever it is necessary to colour **Ultratop Loft F** and **Ultratop Loft W**, both in the white and in the natural versions.

## COLOURS

**Ultratop Easycolor** are available in different colours to satisfy the most varied aesthetic needs. For the complete list of available colours contact our technical assistance.

## RECOMMENDATIONS

- Do not use **Ultratop Easycolor** if the temperature is lower than +5°C or higher than +35°C.
- Each tin of **Ultratop Easycolor** must be mixed with 5 kg of **Ultratop Loft F** or **Ultratop Loft W**. If the cementitious mortar is supplied in 20 kg bags, it is recommended to split it into four separate batches of 5 kg each.
- **Ultratop Easycolor** must be only used to colour **Ultratop Loft** range of products.

## APPLICATION PROCEDURE

Mix **Ultratop Easycolor** with **Ultratop Loft F** or **Ultratop Loft W** in a clean, suitably sized container at a rate of one 1.5 l can of **Ultratop Easycolor** every 5 kg of **Ultratop Loft F** or **Ultratop Loft W** cementitious formulation. Clean water at a rate of up to 4% by weight may also be added, depending on actual site conditions (temperature and relative humidity) and the consistency required.

Mix the compound with a low-speed electric mixer to form an even lump-free mixture.

Please refer to the corresponding Technical Data Sheet for the correct preparation of **Ultratop Loft F** and **Ultratop Loft W**.

## CLEANING

Clean tools used to mix **Ultratop Easycolor** immediately after use with plenty of running water.

## CONSUMPTION

One 1.5 l can every 5 kg of **Ultratop Loft F** or **Ultratop Loft W**.

## PACKAGING

1.5 l cans.

## STORAGE

18 months in its original sealed packaging, in a dry place at a temperature of +5°C to +30°C.

## SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website [www.mapei.com](http://www.mapei.com).

PRODUCT FOR PROFESSIONAL USE.

## TECHNICAL DATA (typical values)

### PRODUCT IDENTITY

Consistency:	liquid
Colour:	various
Density:	from 1.0 to 1.05 g/cm <sup>3</sup> depending on colour

### APPLICATION DATA (at +23°C - 50% R.H.)

Application temperature:	+5°C to +35°C
--------------------------	---------------

## WARNING

*Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.*

**Please refer to the current version of the Technical Data Sheet, available from our website [www.mapei.com](http://www.mapei.com)**

## LEGAL NOTICE

*The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.*

*The most up-to-date TDS can be downloaded from our website [www.mapei.com](http://www.mapei.com).*

**ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.**

## TECHNICAL SPECIFICATIONS

Supply and installation of pre-dispersed selected pigments (such as **Ultratop Easycolor** by Mapei S.p.A.) to be used to colour cementitious mortars for the creation of decorative solution for floors and vertical surfaces in general.

The product must have the following characteristics:

Consistency:	liquid
Density:	from 1.0 a 1.05 g/cm <sup>3</sup> depending on the colour

**Mapei S.p.A.**

Via Cafiero, 22, 20158, Milano



+39-02-376731



[www.mapei.com](http://www.mapei.com)



[mapei@mapei.it](mailto:mapei@mapei.it)

**6794-10-2024 en (IT)**

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

